

40-5 suction-cup
is a long, stable
thin, sealing lip with
raised working
changeovers
s and dimensions,
high initial flow, the
tipping speeds and
ments. The bag-
contact food items
lications. With a wide
to 392 deg F, the
products including
k below on the cup
with liquid, viscous
ns, the co. states.



Shrink wrapper/bundler TANGO 24 shrink wrapper is a low cost, compact, print-registered shrink bundler that offers three different, interchangeable infeeds: An inline infeed; an inline flood infeed; and a side infeed. These modules can be changed in less than 10 min. The shrink wrapper uses an intermittent-motion wrapping assembly that doesn't use a seal bar and is capable of running up to 20 bundles/min using clear, pattern-printed or print-registered film.

Polypack Inc., 727/578-5000.

www.polypack.com



I/O adapter The wireless POINT I/O adapter is a high-speed, standards-based 802.11-g module that supports the co.'s Integrated Wireless Architecture™, combining Rockwell Automation's field proven I/O and the co.'s wireless technology and support. The co. reports that the adapter provides a familiar programming experience to users by incorporating the I/O adapter's Add-On Profile (AOP) in RSLogix 5000.

ProSoft Technology Inc.,

661/716-5257.

www.prosoft-technology.com



P-S labeler Label-Vantage™ p-s labeler can handle full- and partial-wraparound front/back-label panel applications on plastic, metal, fiber and glass containers. The machine can be operated in three shifts and features a one-piece, heavy-duty, stainless-steel welded uni-frame that allows it to easily accept a second applicator head for front and back labeling. A color touchscreen control system allows for easy interfacing and setup of label countdown, bottle speed, motor speeds and recipe settings with an onscreen keyboard for alphanumeric naming. Also features a European-designed label applicator capable of reaching speeds up to 40 m/min.

KAPS-ALL Packaging Systems,

631/727-0300. www.kapsall.com